

Model		7180		7240		7300	
Configuration		Tow Behind	Tow Between	Tow Behind	Tow Between	Tow Behind	Tow Between
Capacity	- Total	180 bu (6,550 <i>ℓ</i> )		240 bu (8,730 <i>ℓ</i> )		300 bu (10,910 <i>ℓ</i> )	
	- Tanks	2		2		2	
	- Splits	71/109 b (2,580/3,970 <i>ℓ</i> )		95/145 bu (3,460/5,270 <i>ℓ</i> )		120/180 bu (4,360/6,550 <i>ℓ</i> )	
Dimensions	- Width	11' 10" (3.61 m)	11' 10" (3.61 m)	12' (3.66 m)	12' (3.66 m)	12' (3.66 m)	12' (3.66 m)
	- Length with auger	22' 5" (6.83 m)	25' 3" (7.70 m)	25' 8" (7.82 m)	26' 10" (8.18 m)	25' 8" (7.82 m)	26' 10" (8.18 m)
	- Height	10' 9" (3.28 m)	10' 9" (3.28 m)	11' 4" (3.45 m)	11' 4" (3.45 m)	12' (3.66 m)	12' (3.66 m)
	- Weight with auger	5,720 lbs (2,574 kg)	5,420 lbs (2,439 kg)	7,315 lbs (3,292 kg)	6,825 lbs (3,071 kg)	7,770 lbs (3,479 kg)	7,325 lbs (3,296 kg)
Fan	- Impeller	13" (33 cm) Diameter					
	- Operating rpm	Up to 5,000 rpm					
	- Hydraulic Drive	Closed Centre or Closed Centre Load Sensing systems required.					
		12cc piston type orbit motor (Maximum 15.5 U.S. gal./min.) (59 l/min) (Minimum 2100 p.s.i.) (14,469 kPa)					
Tires	- Standard (Front)	(1) 21.5 x 16.1 - 6 ply rating	N/A	(2) 21.5 x 16.1 - 6 ply rating	N/A	(2) 21.5 x 16.1 - 10 ply rating	N/A
	- Standard (Rear)	(2) 21.5 x 16.1 - 6 ply rating	(2) 21.5 x 16.1 - 6 ply rating	(2) 23.1 x 26 - 12 ply rating	(2) 23.1 x 26 - 12 ply rating	(2) 23.1 x 26 - 12 ply rating	(2) 23.1 x 26 - 12 ply rating
	- Optional (Front)	(1) 21.5 x 16.1 Rice - 8 ply rating	N/A	(2) 21.5 x 16.1 Rice - 12 ply rating	N/A	(2) 21.5 x 16.1 Rice - 12 ply rating	N/A
	- Optional (Rear)	(2) 21.5 x 16.1 Rice - 8 ply rating	(2) 21.5 x 16.1 Rice - 8 ply rating	(2) 23.1 x 26 Rice - 10 ply rating	(2) 23.1 x 26 Rice - 10 ply rating	(2) 23.1 x 26 Rice - 10 ply rating	(2) 23.1 x 26 Rice - 10 ply rating
	- Three Point Hitch	N/A	(2) 18.4 x 26 - 10 ply rating	N/A	(2) 23.1 x 26 - 12 ply rating	N/A	N/A
Loading Auger - Standard		7" Diameter x 18.5' Long (0.18 m x 5.64 m)		8" Diameter x 20' Long (0.2 m x 6.1 m)		8" Diameter x 20' Long (0.2 m x 6.1 m)	
Metering System		Easy Clean Out System, 8 primaries, single shoot 21 - 80 runs, double shoot 42 - 160 runs, Primary hose dia. - 2 1/2" (6.4 cm), Secondary hose dia. - 15/16" (2.4 cm)					
- Meter Drive		Ground drive mechanism with electric clutch controlled from cab. Optional second clutch for individual meter shaft control. Optional fertilizer bander kit for easy one transmission rate setting.					
Monitor		Standard - (Shaft Motion (3), Bin Level (3), Fan Speed, Acre Tally, Ground Speed) Optional - (Seed Flow)					
Safety Lights / Safety Chain		Standard					
Options		- Tow Between models Tank Access Screens, Mechanical Acre Meter (Mech. Drive), Three Point Hitch for 7180 & 7240 only (Categories II, III, III-N)					
- Tow Behind models		Tank Access Screens, Mechanical Acre Meter (Mech. Drive), Trailing Hitch, Hitch Stand, and (Front Wheel Scraper for 7180 Front Wheel Only)					
- Third Tank		Optional (40 cu. ft.) (1,129 <i>ℓ</i> )		Optional (40 cu. ft.) (1,129 <i>ℓ</i> ) (N/A on 7300 Tow Between)			
- Granular Applicator		N/A		Optional (40 cu. ft.) (1,129 <i>ℓ</i> ) (N/A on 7300 Tow Between)			