

Configuration	Tow Between	Tow Behind
Rear Tow Hitch - 9365 to 9650	Standard (Max 26,000 lb Draft Load) (Max 11,818 kg Draft Load)	Optional (9365 to 9650) (Max 15,000 lb Draft Load) (Max 6,818 kg Draft Load)
Rear Tow Hitch - 9800	N/A	Standard (Max 26,000 lb Draft Load) (Max 11,818 kg Draft Load)
Hitch Stand	N/A	Optional
Fan Impeller Diameter	17" (43 cm) - Up to 5,000 r.p.m.	
Hydraulic Fan Drive (Closed Centre or Closed Centre Load Sensing systems required) Hydraulic requirements for Air Cart only at Rated Fan Speed.	16cc - piston type orbit motor 21 U.S. gal./min. (80 l/min) at 2,750 p.s.i. (18,960 kpa) Dual Fans require 42 U.S. gal./min. (160 l/min) VRT requires an additional 5.5 U.S. gal/min (21 l/min)	
High Flow Hydraulic Kit	Standard	
Loading Auger	Standard (10" Dia) (25.4 cm Dia) Optional - Conveyor(16") (40.6 cm) Optional - Hydraulic Assist	
Metering - Ground Driven - Variable Rate (VRT) - GPS Compatible VRT	Standard Optional - Topcon Monitor Optional - Topcon Monitor	
Meter Shut Off	Electric	
Number Secondary Runs - Single Shoot	21 to 99 (9800 will do up to 110)	
Number Secondary Runs - Double Shoot	42 to 198 (9800 will do up to 220)	
Number Secondary Runs - Triple Shoot	Subject to availability	
Primary Hose - Diameter	2 1/2" (6.4 cm)	
Secondary Hose - Diameter	Standard - 15/16" (2.4 cm) Optional - 1 1/4" (3.2 cm)	
Easy Clean Out System	Standard	
Meter Drive Option -Second Clutch (For spot fertilizing on the go)	Standard (Ground Drive Only)	
Monitor - (Shaft Motion (4), Bin Level (4), Fan Speed (2), Acre Tally, Ground Speed)	Standard Optional Seed Flow	
Work Switch (Mounted to Seeding Machine)	Optional	
Mechanical Acre Meter	Optional (Ground Drive Only)	

Tank Capacity							
Model	Front Tank	Mid 1 Tank	Mid 2 Tank	Rear Tank	Total	Weight Tow Behind	Weight Tow Between
9365 2 Tank	182 bu 226.5 cu ft 6414 litres	N/A	N/A	182 bu 226.5 cu ft 6414 litres	364 bu 12828 litres 50/50 Split	10900 lbs 4944 kg	14100 lbs 6396 kg
9450 3 Tank	182 bu 226.5 cu ft 6414 litres	86 bu 107 cu ft 3030 litres	N/A	182 bu 226.5 cu ft 6414 litres	450 bu 15858 litres 40/19/40 Split	11900 lbs 5398 kg	15100 lbs 6849 kg
9535 4 Tank	182 bu 226.5 cu ft 6414 litres	86 bu 107 cu ft 3030 litres	86 bu 107 cu ft 3030 litres	182 bu 226.5 cu ft 6414 litres	536 bu 18888 litres 34/16/16/34	13000 lbs 5897 kg	N/A
9445 2 Tank	221 bu 275 cu ft 7788 litres	N/A	N/A	221 bu 275 cu ft 7788 litres	442 bu 15576 litres 50/50 Split	17300 lbs 7847 kg	20000 lbs 9072 kg
9550 3 Tank	221 bu 275 cu ft 7788 litres	107 bu 133 cu ft 3772 litres	N/A	221 bu 275 cu ft 7788 litres	549 bu 19348 litres 40/19/40 Split	18000 lbs 8165 kg	20700 lbs 9389 kg
9650 4 Tank	221 bu 275 cu ft 7788 litres	107 bu 133 cu ft 3772 litres	107 bu 133 cu ft 3772 litres	221 bu 275 cu ft 7788 litres	656 bu 23120 litres 34/16/16/34	18700 lbs 8482 kg	21400 lbs 9707 kg
9800 4 Tank	265 bu 330 cu ft 9339 litres	133 bu 166 cu ft 4700 litres	133 bu 166 cu ft 4700 litres	133 bu 166 cu ft 4700 litres	284 bu 353 cu ft 10008 litres	815 bu 28747 litres 33/16/16/35	24000 lbs 10890 kg

Tire Specifications								
Tire	Style	Rating	Pressure					
			BT 9365	BH 9365	BH 9535	BH 9445	BT 9445	BH 9550
500/70 R24 Front Castor	Lug	LI 157	-	25 psi	-	-	-	-
28LR26 Quad Steer	Lug	165 A8	-	18 psi	18 psi	18 psi	-	-
800/65 R32	Lug	LI 172	20 psi	20 psi	-	-	-	20 psi
800/65 R32 Dual Wheels	Lug	LI 172	-	-	-	20 psi	20 psi	20 psi
900/60 R32	Lug	176 A8	17 psi	17 psi	26 psi	26 psi	-	-
520/85 R38 Dual Wheels	Lug	155 A8	-	20 psi	20 psi	20 psi	-	-

*BH - Tow Behind only *BT - Tow Between only