

Base Size	3 Frame Models				5 Frame Models					
	25' (7.62 m)	31' (9.45 m)	41' (12.5 m)	51' (15.54 m)	61' (18.59 m)	71' (21.64 m)	80' (24.38 m)	86' (26.21 m)	90' (27.43 m)	
Weight	- 10" Spacing	14,738 lb 6,685 kg	16,025 lb 7,269 kg	20,928 lb 9,470 kg	24,622 lb 11,168 kg	31,392 lb 14,239 kg	35,441 lb 16,109kg	NA NA	NA NA	NA NA
	- 12" Spacing 30.5 cm Spacing	13,933 lb 6,320 kg	15,155 lb 6,874 kg	19,572 lb 8,856 kg	23,137 lb 10,495 kg	29,358 lb 13,317 kg	33,264 lb 15,120 kg	38,140 lb 17,300 kg	41,000 lb 18,600 kg	43,000 lb 19,505 kg
Working Width	- 10" (25.4 cm) Spacing	25' (7.62m)	30' (9.14m)	41.67' (12.7m)	50' (15.24m)	60' (18.29m)	70' (21.34m)	NA	NA	NA
	- 12" (30.5 cm) Spacing	25' (7.62m)	31' (9.45m)	41' (12.5m)	51' (15.54m)	61' (18.59m)	71' (21.64m)	80' (24.38m)	86' (26.21 m)	90' (27.43 m)
Number of Shanks	- 10" (25.4 cm) Spacing	30	36	50	60	72	84	NA	NA	NA
	- 12" (30.5 cm) Spacing	25	31	41	51	61	71	80	86	90
Frame Width	- Main	5' (1.524m)	5' (1.524m)	16' (4.88m)	16' (4.88m)	16' (4.88m)	16' (4.88m)	21' (6.40m)	21' (6.40m)	21' (6.40m)
	- Wing Inner	10' (3.048m)	13' (3.962m)	12' (3.66m)	17.5' (5.334m)	12' (3.66m)	15' (4.57m)	15' (4.57m)	15' (4.57m)	15' (4.57m)
Transport Position	- Width	9' 10" (3m)	9' 10" (3m)	20' 6" (6.25m)	20' 6" (6.25m)	20' 6" (6.25m)	20' 6" (6.25m)	25' (7.62m)	25' (7.62m)	25' (7.62m)
	- Height	13' 6" (4.12m)	15' 11" (4.85m)	15' 2" (4.62m)	15' 2" (4.62m)	15' 2" (4.62m)	17' 10" (5.44m)	17' 10" (5.44m)	17' 10" (5.44m)	17' 10" (5.44m)
	- Length	31' 6" (9.6m)	31' 6" (9.6m)	31' 6" (9.6m)	31' 6" (9.6m)	34' 10" (10.62m)	34' 10" (10.62m)	34' 10" (10.62m)	34' 10" (10.62m)	34' 10" (10.62m)
Tires	- Main Frame Wheels	(4)12.5Lx15 FI Load Range F	(4)12.5Lx15 FI Load Range F	(8) 11Lx15 FI Load Range F	(8) 11Lx15 FI Load Range F	(8) 12.5L x15 FI Load Range F	(8) 12.5Lx15 FI Load Range F	(8) 16.5x16.1 FI Load Range E	(8) 16.5x16.1 FI Load Range E	(8) 16.5x16.1 FI Load Range E
	- Wing Frame Front Castor Wheels	Single Castor (2) 12.5SLx15	Single Castor (2) 12.5SLx15 12 Ply Rating	Dual Castor (4) 11SLx15 12 Ply Rating	Dual Castor (4) 11SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating
	- Wing Frame Rear Wheels	(1 per wing) (2) 12.5SLx15 12 Ply Rating	(1 per wing) (2) 12.5SLx15 12 Ply Rating	(1 per wing) (2) 11SLx15 12 Ply Rating	(1 per wing) (2) 11SLx15 12 Ply Rating	(1 per wing) (4) 12.5SLx15 12 Ply Rating	(1 per wing) (4) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating
	- Optional Main Frame Wheels	NA	NA	NA	NA	(8) 16.5x16.1 FI Load Range E	(8) 16.5x16.1 FI Load Range E	NA	NA	NA
Opener	- Trip Out Force	Minimum 300 lbs at 450 psi (3102 kPa) to Maximum 700 lbs (317 kg) at 1200 psi (8274 kPa)								
	- Packing Force	80 lbs to 200 lbs (36 kg - 91 kg)								
	- Packer Wheel	4.50" x 16" Semi Pneumatic Otico tire 4.80" x 16" Semi Pneumatic or Pneumatic 5.50" x 16" Semi Pneumatic Otico tire 5.50" x 16" Semi-Pneumatic 4.00" x 16" "V" Crown								
	Opener to Ground Clearance	12" (30.5 cm)								
Frame to Ground Clearance	32" (81 cm)									
Frame Depth	94" (238.8 cm) center to center									
Rank to Rank Spacing	47" (119.4 cm) center to center									
Number of Ranks	3 Rows									
Shank to Shank Spacing	30" (76.2 cm) on 10" (25.4 cm) Spacing									
	36" (91.4 cm) on 12" (30.5 cm) Spacing									
Weight Kit	Optional									
Safety Lights	Standard									
Hitch Clevis	Standard - Category 4 Optional - Category 5									
Safety Chain	Standard									