

Base Model	Ext'd Model	Working Width			Number of Shanks			Transport			Weight with 755 LH Trip		
		12"	10"	9"	12"	10"	9"	Width	Height		12"	10"	9"
		30.5 cm	25.4 cm	22.9 cm	30.5 cm	25.4 cm	22.9 cm		12"	10"	9"	30.5 cm	25.4 cm

3 Section: Regular Transport

Base Model	Ext'd Model	Working Width			Number of Shanks			Transport			Weight with 755 LH Trip			
		12"	10"	9"	12"	10"	9"	Width	Height		12"	10"	9"	
23'	7 m	23'	24'	23.5'	23	29	31		17' 7"	11'	11' 7"	11' 1"	11,575 lb	12,665 lb
		7.01 m	7.31 m	7.16 m				5.36 m	3.35 m	3.53 m	3.38 m	5,261 kg	5,757 kg	5,593 kg
	25'	25'	26'	25'	25	31	33	17' 7"	12'	12' 5"	11' 10"	12,045 lb	13,190 lb	12,775 lb
		7.62 m	7.62 m	7.62 m				5.36 m	3.66 m	3.78 m	3.61 m	5,475 kg	5,995 kg	5,807 kg
	29'	29'	31'	29.5'	29	37	39	17' 6"	14'	14' 8"	14'	13,180 lb	13,945 lb	14,110 lb
		8.84 m	9.45 m	8.99 m				5.33 m	4.27 m	4.47 m	4.27 m	5,991 kg	6,339 kg	6,414 kg
	31'	31'	32.5'	31'	31	39	41	17' 6"	14'	10"	15' 6"	13,650 lb	14,470 lb	14,580 lb
		9.45 m	9.45 m	9.45 m				5.33 m	4.52 m	4.72 m	4.52 m	6,205 kg	6,577 kg	6,627 kg
	33'	33'	34'	32.5'	33	41	43	17' 6"	15'	10"	16' 4"	14,230 lb	15,095 lb	15,155 lb
		10.06 m	10.06 m	10.36 m				5.33 m	4.83 m	4.98 m	4.75 m	6,468 kg	6,861 kg	6,889 kg

3 Section: Wide Transport

Base Model	Ext'd Model	Working Width			Number of Shanks			Transport			Weight with 755 LH Trip			
		12"	10"	9"	12"	10"	9"	Width	Height		12"	10"	9"	
32'	9.75 m	32'	34'	32.5'	32	41	43		20' 6"	14'	14' 8"	14'	14,060 lb	14,910 lb
		9.75 m	10.36 m	9.91 m				6.25 m	4.27 m	4.47 m	4.27 m	6,391 kg	6,777 kg	6,832 kg
	34'	34'	36'	34'	34	43	45	20' 6"	14'	10"	15' 6"	14,530 lb	15,435 lb	15,500 lb
		10.36 m	10.36 m	10.97 m				6.25 m	4.52 m	4.72 m	4.52 m	6,605 kg	7,016 kg	7,045 kg
	36'	36'	37.5'	35.5'	36	45	47	20' 6"	15'	10"	16' 4"	15,110 lb	16,060 lb	16,075 lb
		10.97 m	10.97 m	11.43 m				6.25 m	4.83 m	4.98 m	4.75 m	6,868 kg	7,300 kg	7,307 kg
	38'	38'	41'	38.5'	38	49	51	20' 2"	17'	18' 1"	17'	15,190 lb	16,185 lb	16,335 lb
		11.58 m	12.50 m	11.73 m				6.15 m	5.18 m	5.51 m	5.18 m	6,905 kg	7,357 kg	7,425 kg
	40'	40'	42.5'	40'	40	51	53	20' 2"	17' 8"	18' 11"	17' 8"	15,660 lb	16,710 lb	16,805 lb
		12.19 m	12.19 m	12.95 m				6.15 m	5.38 m	5.77 m	5.38 m	7,118 kg	7,595 kg	7,639 kg
	42'	42'	44'	41.5'	42	53	55	20' 2"	18' 8"	19' 9"	18' 5"	16,240 lb	17,335 lb	17,380 lb
		12.80 m	12.80 m	13.41 m				6.15 m	5.69 m	6.02 m	5.61 m	7,382 kg	7,880 kg	7,900 kg

5 Section

Base Model	Ext'd Model	Working Width			Number of Shanks			Transport			Weight with 755 LH Trip			
		12"	10"	9"	12"	10"	9"	Width	Height		12"	10"	9"	
44'	13.41 m	44'	47.5'	44.5'	44	57	59		22'	16' 2"	16' 8"	16' 2"	21,195 lb	22,550 lb
		13.41 m	14.48 m	13.56 m				6.71 m	4.93 m	5.08 m	4.93 m	9,634 kg	10,250 kg	10,264 kg
	46'	46'	49'	46'	46	59	61	22'	16' 2" <td>16' 8"</td> <td>16' 2"</td> <td>21,665 lb</td> <td>23,075 lb</td> <td>23,050 lb</td>	16' 8"	16' 2"	21,665 lb	23,075 lb	23,050 lb
		14.02 m	14.02 m	14.02 m				6.71 m	4.93 m	5.08 m	4.93 m	9,848 kg	10,489 kg	10,477 kg
	50'	50'	54'	50.5'	50	65	67	23' 3"	18' 8"	19' 5"	18' 5"	22,855 lb	24,385 lb	24,435 lb
		15.24 m	15.24 m	16.46 m				7.09 m	5.69 m	5.92 m	5.61 m	10,389 kg	11,084 kg	11,107 kg
	52'	52'	56'	52'	52	67	69	23' 3"	18' 8"	19' 5"	18' 5"	23,325 lb	24,910 lb	24,905 lb
		15.85 m	15.85 m	17.07 m				7.09 m	5.69 m	5.92 m	5.61 m	10,602 kg	11,323 kg	11,320 kg
	56'	56'	61'	56.5'	56	73	75	24' 3"	18' 8"	19' 5"	18' 5"	23,425 lb	25,180 lb	25,150 lb
		17.07 m	17.07 m	18.59 m				7.39 m	5.69 m	5.92 m	5.61 m	10,648 kg	11,445 kg	11,432 kg
	58'	58'	62.5'	58'	58	75	77	24' 3"	18' 8"	19' 5"	18' 5"	23,895 lb	25,705 lb	25,620 lb
		17.68 m	17.68 m	19.05 m				7.39 m	5.69 m	5.92 m	5.61 m	10,861 kg	11,684 kg	11,645 kg
	60'	60'	64'	59.5'	60	77	79	24' 3"	18' 8"	19' 5"	18' 5"	24,475 lb	26,330 lb	26,195 lb
		18.29 m	18.29 m	19.51 m				7.39 m	5.69 m	5.92 m	5.61 m	11,125 kg	11,968 kg	11,907 kg

Trip Mechanism	Shank	Centres	Sweep	Trip Force
400 Spring Cushion	1" (2.54 cm) x 2" (5.1 cm)	fits 47 Degree tillage tools.	27" (68.6 cm)	400 lb (180 kg)
550 Spring Cushion	1" (2.54 cm) x 2" (5.1 cm)	fits 47 Degree tillage tools.	27" (68.6 cm)	550 lb (248 kg)
755 LH Automatic Trip	1-1/4" (3.18 cm) x 2" (5.1 cm)	fits 50 Degree tillage tools.	30" (76.2 cm)	750 lb (340 kg)

Overall Length	26' (7.93 m) on all Models
Frame Depth	102" (2.59 m) on all Models
Rows	4 Rows on all Models
Standard	Safety Lights, Safety Chain
Options	Mud Scrapers, Shank Mounted Ground Rod, Mounted Packers, and Mounted Harrows

Base Model	Ext'd Model	FRAME CONFIGURATIONS									
		Main Frame		Inner Wings			Outer Wings		Extensions		Tires
		12'	15'	6'	9'	12'	6'	9'	2 Shank	4 Shank	See Below
23											I
7 m											I
	25										I
											I
	29										II
											II
	31										II
											II
	33										II
											II
	32										II
											II
	34										II
											II
	36										II
											II
	38										II
											II
	40										II
											II
	42										II
											II
	44										III
											III
	46										III
											III
	50										III
											III
	52										III
											III
	56										III
											III
	58										III
											III
	60										III
											III

TIRE CONFIGURATIONS	
Tire - I	Main Frame (4) 9.5L x 15FI Load Range D
	Wing Frame (2 per frame) 9.5L x 15FI Load Range D
	Main Gauge Wheel (2) 9.5L x 15FI Load Range D
	Wing Gauge Wheel (1 per frame) 9.5L x 15FI Load Range D
Tire - II	Main Frame (4) 11L x 15FI Load Range D
	Wing Frame (2 per frame) 11L x 15FI Load Range D
	Main Gauge Wheel (2) 11L x 15FI Load Range D
	Wing Gauge Wheel (1 per frame) 11L x 15FI Load Range D
Tire - III	Main Frame (4) 11L x 15FI Load Range F
	Wing Frame (2 per frame) 11L x 15FI Load Range F
	Main Gauge Wheel (2) 11L x 15FI Load Range F
	Wing Gauge Wheel (1 per frame) 11L x 15FI Load Range F