

Base Size	3 Frame Models			5 Frame Models		
	29' (8.84 m)	34' (10.36 m)	39' (11.89 m)	49' (14.94 m)	55' (16.77 m)	60' (18.29 m)
Weight (3 1/2" Steel Packers with Edge-On Shank)						
- 7 1/2" Spacing 19.0 cm Spacing	14,962 lbs. 6,801 kg	17,039 lbs. 7,745 kg	18,952 lbs. 8,615 kg	25,257 lbs. 11,480 kg	N/A N/A	N/A N/A
- 10" Spacing 25.4 cm Spacing	13,566 lbs. 6,166 kg	15,025 lbs. 6,830 kg	16,946 lbs. 7,703 kg	22,550 lbs. 10,250 kg	26,981 lbs. 12,264 kg	28,801 lbs. 13,091 kg
- 12" Spacing 30.5 cm Spacing	12,330 lbs. 5,605 kg	14,151 lbs. 6,432 kg	16,003 lbs. 7,274 kg	20,909 lbs. 9,504 kg	25,357 lbs. 11,526 kg	27,294 lbs. 12,406 kg
Working Width						
- 7 1/2" (19.0 cm) Spacing	29' 5" (8.97 m)	34' 5" (10.49 m)	39' 5" (12.01 m)	49' 5" (15.06 m)	N/A	N/A
- 10" (25.4 cm) Spacing	30' (9.14 m)	35' (10.67 m)	40' (12.19 m)	50' (15.24 m)	55' (16.76 m)	60' (18.29 m)
- 12" (30.5 cm) Spacing	29' (8.84 m)	35' (10.67 m)	41' (12.50 m)	49' (14.93 m)	55' (16.76 m)	61' (18.59 m)
Number of Shanks						
- 7 1/2" (19.0 cm)	47	55	63	79	N/A	N/A
- 10" (25.4 cm)	36	42	48	60	66	72
- 12" (30.5 cm)	29	35	41	49	55	61
Frame Width						
- Main	14' 6" (4.42 m)	14' 6" (4.42 m)	14' 6" (4.42 m)	14' 6" (4.42 m)	14' 6" (4.42 m)	14' 6" (4.42 m)
- Inner Wing	7' 6" (2.29 m)	10' (3.05 m)	12' 6" (3.81 m)	10' (3.05 m)	12' 6" (3.81 m)	12' 6" (3.81 m)
- Outer Wing	N/A	N/A	N/A	7' 6" (2.29 m)	7' 6" (2.29 m)	10' (3.05 m)
Overall Length	25' 8" (7.82 m)	25' 8" (7.82 m)	25' 8" (7.82 m)	29' 7" (9.02 m)	29' 7" (9.02 m)	29' 7" (9.02 m)
Transport Position						
- Width	19' 10" (6.03 m)	19' 10" (6.03 m)	19' 10" (6.03 m)	22' 6" (6.86 m)	24' 6" (7.47 m)	24' 6" (7.47 m)
- Height	12' 1" (3.68 m)	14' 1" (4.29 m)	16' 7" (5.06 m)	17' 6" (5.33 m)	17' (5.18 m)	17' (5.18 m)
Tires						
- Main Frame Castor Wheel	(2) 11L x 15 FI Load Range D	(2) 11L x 15 FI Load Range D	(2) 11L x 15 FI Load Range D	(2) 11L x 15 FI Load Range D	(2) 12.5L x 15 FI Load Range F	(2) 12.5L x 15 FI Load Range F
- Inner Wing Frame Castor Wheel	(1 per wing) (2) 11L x 15 6 ply rating	(1 per wing) (2) 11L x 15 6 ply rating	(1 per wing) (2) 11L x 15 6 ply rating	(1 per wing) (2) 11L x 15 6 ply rating	(2 per wing) (4) 11L x 15 6 ply rating	(2 per wing) (4) 11L x 15 6 ply rating
- Outer Wing Frame Castor Wheel (1 per wing)	N/A	N/A	N/A	(2) 11L x 15 6 ply rating	(2) 11L x 15 6 ply rating	(2) 11L x 15 6 ply rating
- Main Frame Transport Wheels	(4) 11L x 15 FI Load Range D 6 Bolt Hub	(4) 11L x 15 FI Load Range D 6 Bolt Hub	(4) 11L x 15 FI Load Range F 8 Bolt Hub	(4) 11L x 15 FI Load Range F 8 Bolt Hub	(4) 12.5L x 15 FI Load Range F 8 Bolt Hub	(4) 12.5L x 15 FI Load Range F 8 Bolt Hub
Dual Castor Wheels on Wings	Optional	Optional	Optional	Optional	Standard on Inner Wing Optional for Outer Wing	
Number of Ranks	7 1/2" (19.0 cm) Spacing - 4 row "Z" Pattern 10" (25.4 cm) & 12" (30.5 cm) Spacing - 4 row					
Trip Mechanism	400 lb (180 kg) Spring Cushion Trip with 1 (2.54 cm) x 2" (5.1 cm) shank					
Shank Options	Forged Edge-On Conventional 'C' Shank (1 3/4" (4.4 cm) hole spacing) (47 Degree tillage tools)					
Packer Wheel Options	3 1/2" (8.9 cm) Steel or Rubber - (7 1/2" (19.0 cm), 10" (25.4 cm) & 12" (30.5 cm) Spacing) 4 1/2" (11.4 cm) Steel or Rubber - (10" (25.4 cm) & 12" (30.5 cm) Spacing ONLY)					
Frame to Opener	Vertical Clearance - 27 1/2" with Regular Hoe Point - 30 1/2" with Double Shoot/Knife Openers					
Rank to Rank Spacing	24" (61.0 cm)					
Shank to Shank Spacing	30" (76.2 cm) on 7 1/2" (19.0 cm) & 10" (25.4 cm) spacing, 36" (91.4 cm) on 12" (30.5 cm) spacing					
Frame Depth	76" (1.93 m) (4 ranks)					
2-Bar Harrows	Optional (3 Row 10" (25.4 cm) Spacing ONLY)					
Coulters	Optional - Front Row Mount on 30" (76.2 cm) Centres - (20" (50.8 cm) diameter)					
- Trash Cutting (Rippled or Plain)						
- Fertilizer (Plain)	Optional - Random Mounting on 20" (50.8 cm) Centres - (20" (50.8 cm) diameter) (N/A on 55 and 60 ft)					
Packer Mud Scrapers	Optional (For both Steel and Rubber Packers)					
Rock Deflectors	Optional (7 1/2" (19.0 cm), 10" (25.4 cm) & 12" (30.5 cm) Spacing)					
Safety Lights	Standard					
Safety Chain	Standard					