

Base Size	3 Frame Models		5 Frame Models				
	40' (12.19 m)		50' (15.24 m)		60' (18.29)		
Weight - Single Shoot	- 7.5" Spacing 19 cm Spacing	29847 lbs 13538 kg	37360 lbs 16946 kg	44872 lbs 20354 kg			
	- 10" Spacing 25.4 cm Spacing	26599 lbs 12065 kg	33300 lbs 15105 kg	40000 lbs 18144 kg			
	- 15" Spacing 38.1 cm Spacing	23554 lbs 10684 kg	29443 lbs 13355 kg	35331 lbs 16026 kg			
Working Width	- 7.5" (19 cm)	38' 4.5" (12 m)	49' 4.5" (15.05 m)	59' 4.5" (18.10 m)			
	- 10" (25.4 cm)	39' 2" (11.93 m)	49' 2" (14.99 m)	59' 2" (18.03 m)			
	- 15" (38.1 cm)	40' (12.19 m)	50' (15.24 m)	60' (18.29 m)			
Number of Openers - Single Shoot	- 7.5" (19 cm)	63	79	95			
	- 10" (25.4 cm)	47	59	71			
	- 15" (38.1 cm)	32	40	48			
Number of Openers - Double Shoot	- 7.5" (19 cm)	NA	NA	NA			
	- 10" (25.4 cm)	71	89	107			
	- 15" (38.1 cm)	NA	NA	NA			
Frame Width	- Main	14' 3.5" (4.356m)	14' 3.5" (4.356m)	14' 3.5" (4.356m)			
	- Wing Inner	11' 11.5" (3.645m)	11' 11.5" (3.645m)	11' 11.5" (3.645m)			
	- Wing Outer	NA	5' 4.84" (1.647m)	9' 11.25" (3.029m)			
Transport Position	- Width	20' 3" (6.17m)	20' 3" (6.17m)	20' 3" (6.17m)			
	- Height	15' 11" (4.85 m)	15' 11" (4.85 m)	15' 11" (4.85 m)			
	- Length	31' 7" (9.63 m)	35' 8" (10.87 m)	35' 8" (10.87 m)			
Tires	- Main Frame Wheels	(8) 16.5x16.1 FI Load Range E	(8) 16.5x16.1 FI Load Range E	(8) 16.5x16.1 FI Load Range E			
	- Wing Frame Front Castor Wheels	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15			
	- Wing Frame Rear Wheels	(2 per wing) (8) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating			
Opener	- Disc Down Force	Adjustable from 200 lbs (90.7 kg) to a maximum of 7.5" Spacing – 465 lbs* (210.9 kg)* 10" Spacing – 550 lbs* (249.5 kg)* 15" Spacing – 690 lbs (313 kg) *Limited by available frame weight					
	- Packing Force	Increases proportionally with Disc Down Force - 66 lbs to 150 lbs (30 kg - 68 kg)					
	- Disc Size	1/4 x 20" (0.63 cm x 50.8 cm) at 5 Degree Angle					
	- Gauge Wheel	4 1/2 x 16 x 3 Spoke					
	- Packer Wheel	4 x 12 Dual Rib					
Opener to Ground Clearance	10" (25.4 cm)						
Rank to Rank Spacing	59" center to center						
Number of Ranks	2 Rows						
Shank to Shank Spacing	15" (38.1 cm) on 7.5" (19 cm) Spacing 20" (50.8 cm) on 10" (25.4 cm) Spacing 30" (76.2 cm) on 15" (38.1 cm) Spacing						
Weight Kit	Optional						
Safety Lights	Standard						
Hitch Clevis	Standard - Category 4		Optional - Category 5				
Safety Chain	Standard						