

EnginePerkins 403D-15TRated Power27.3 kW (36 hp / 37 ps) @ 2,600 rpmNominal Amplitude Range0.45 mmVibration Frequency Range60 HzCentrifugal Force Range33.5 kNWorking Width1,200 mmOperating Weight3,360 kg

6032E ROLLER

6032E SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Tier 3/ Stage III
Manufacturer	Perkins
Model	403D-15T
Rated Power	27.3 kW (36 hp / 37 ps) @ 2,600 rpm
Peak Torque	115 N • m
Number of Cylinders	3
Aspiration	Turbo
Cooling Type	Water

ELECTRICAL SYSTEM	
System Voltage	12 V

30 %
Hydraulic
9.5 km/h
4,100 mm

AXLES	
Steering System	Hydraulic
Steering Method	Articulation
Steering Angle	±30°
Steering Relief Pressure	16 MPa

BRAKES	
Service Brake Type	Hydraulic

HYDRAULIC SYSTEM		
Main Pump Type	Piston Pump	
Main Relief Pressure	18 MPa	

PERFORMANCE (DOUBLE DRIVE, DOUBLE VIBRATION)	
Front Drum Static Linear Load	135 N/cm
Rear Drum Static Linear Load	145 N/cm
Number of Vibrating Drums	2
Nominal Amplitude	0.45 mm
Vibration Frequency	60 Hz
Centrifugal Force	33.5 kN
Number of Amplitude Settings	1

OPERATING WEIGHTS	
Operating Weight	3,360 kg
Weight on Front Drum	1,620 kg
Weight on Rear Drum	1,740 kg

SERVICE CAPACITIES	
Fuel Tank	60 L
Engine Oil	7 L
Hydraulic Oil Tank	54 L
Cooling System	12 L

OPTIONAL EQUIPMENT

Rotary Beacon





